FULLY AUTOMATIC IN-LINE PALLET WRAPPER

Fully Automatic Pallet Wrapper for Integration Into a Line or at End of a Line

A fully automatic, in-line pallet stretch wrapper built into a powered roller conveyor bed — designed for high-volume warehouses and distribution centres that need consistent, hands-free wrapping integrated directly into the packing line.



Fully Automatic Pallet Wrapper for Integration Into a Line or at End of a Line

- **Fully automatic, in-line roller conveyor**
- **Up to 2500kg max load weight (opt.)**
- **1800–2400mm turntable diameter (opt.)**
- **Backed by 35+ years of SWS expertise**

OVERVIEW

Built For High-Volume, In-Line Wrapping

Integrated directly into a powered roller conveyor, this fully automatic pallet wrapper delivers consistent, professional-grade wrapping quality without operator intervention. Adjustable settings and automated film application handle a wide range of load sizes, enhancing load stability while reducing film waste and labour costs — ideal for busy warehouses and distribution centres looking to boost throughput and minimise downtime.

- Fully automatic roller conveyor infeed & outfeed
- Powered pre-stretch film carriage options (fixed or variable) for reduced film usage
- Adjustable turntable diameter, load height & product size to suit a wide range of pallets
- Front & rear forklift access
- Tamper-proof, consistent wrap quality
- Compatible with WMS & ERP systems

SPECIFICATION

Machine & Dimensions

1800 mm	2000 kg	2200 mm	5–11 rpm	1500 kg
TURNTABLE DIAMETER	MAX LOAD WEIGHT	MAX PRODUCT HEIGHT	TURNTABLE SPEED	WEIGHT

Turntable Diameter	1800mm std. — 2200/2400mm optional
Max Load Weight	2000kg std. — 2500kg optional
Turntable Speed	5–11rpm (Ø1800mm) • 5–8rpm (Ø2200–2400mm)
Carriage Up/Down Speed	1.5–5.5 m/min
Max Product Dimensions (L×W)	1200×1200mm std. — 1400×1400 / 1600×1600mm optional
Maximum Product Height	2200mm std. — 2400/2800/3100mm optional
Film Carriage Type	FR (fixed) • PDS (250% fixed pre-stretch) • PVS (150–400% variable pre-stretch)
Forklifting	Front & rear
Max Reel Weight / Size	20kg — 500×300mm
Film Thickness	17–35µm

REQUIRED POWER
3-phase • 3.9kW

SWS
Shrink Wrapping Supplies Ltd
4A Arrow Trading Estate, Corporation Road,
Audenshaw, Manchester, M34 5LR

0161 366 5552
sales@shrinkwrappingsupplies.co.uk

Specifications are correct at time of publication and subject to change without notice. Product images are for illustration purposes and may vary slightly from the machine supplied. © Shrink Wrapping Supplies Ltd.

WARRANTY & SUPPORT

Support You Can Rely On

Warranty & Installation

- 12-month parts-only warranty as standard
- Installation, commissioning and operator training available on all stock machines
- Service contracts available for ongoing maintenance and support

Typical Applications

- eCommerce & fulfilment
- Food & beverage
- Cosmetics & pharmaceuticals
- Engineering & automotive

FILM & SPARES

Also Available	See our full range of pallet wrapping machines, plus stretch film and consumables
Pallet/Stretch Film	Machine stretch film rolls, various gauges & pre-stretch options
Spare Parts	Film carriage rollers, conveyor rollers, drive belts & more
Consumables	Everything to keep your machine running

All available now in our online shop — shrinkwrappingsupplies.co.uk/shop

SWS
Shrink Wrapping Supplies Ltd
4A Arrow Trading Estate, Corporation Road,
Audenshaw, Manchester, M34 5LR

0161 366 5552
sales@shrinkwrappingsupplies.co.uk

Specifications are correct at time of publication and subject to change without notice. Product images are for illustration purposes and may vary slightly from the machine supplied. © Shrink Wrapping Supplies Ltd. • Page 2 of 2