STANDALONE PE SHRINK TUNNEL

Shrink Tunnel — 800 × 600

A high-performance standalone heat tunnel designed specifically for shrinking PE shrink film around cartons, trays and bundled products — built for industrial packaging environments with consistent heat distribution, reliable airflow and uniform shrink results. Available in three chamber lengths to suit different pack sizes and line speeds.



Shrink Tunnel — 800 × 600

Standalone, heat tunnel unit

32–48kW power consumption

800 × 600mm tunnel chamber size

Backed by 35+ years of SWS expertise

OVERVIEW

Built For Larger, Heavier PE-Wrapped Packs

Supplied as a standalone unit, this larger-format PE shrink tunnel is ideal for customers who already operate a sleeve wrapper or sealing machine and need a dependable tunnel to complete the packaging process for bigger, bulkier packs. Suitable for most packing demands including electronics, hardware, plastic, food, printing, pharmaceuticals and construction materials — commonly used for beverages (beer, water, cans, glass bottles) with a tray or carton. Available in three chamber lengths — 1500mm, 1800mm and 2500mm — to match your product size and line speed.

- Optimised specifically for PE shrink film applications
- Delivers strong, even shrinking for heavier or grouped products
- High-efficiency heating elements with forced hot-air circulation for wrinkle-free results
- Heat-resistant conveyor rollers ensure stable product transport
- Variable conveyor speed matches upstream sealing equipment
- Simple controls for fast setup and easy operation

SPECIFICATION

Machine & Dimensions

1900 mm	1200 mm	2500–3500 mm	700 kg	32–48 kW
HEIGHT	WIDTH	LENGTH	WEIGHT	POWER

Tunnel Chamber Size	800mm (W) × 600mm (H) — 3 chamber lengths available, see table
Max Packing Size	600mm (W) × 500mm (H) — max length depends on chamber option, see table
Temperature Range	0–400°C
Workable Table Height	850mm ± 50mm
Capacity	40–60 pcs/min
Conveyor Speed	0–20 m/min
Applicable Films	Polythene

REQUIRED POWER
3-phase • 380V • 50Hz • 32–48kW depending on chamber length option (see table)

SWS
Shrink Wrapping Supplies Ltd
4A Arrow Trading Estate, Corporation Road,
Audenshaw, Manchester, M34 5LR

0161 366 5552
sales@shrinkwrappingsupplies.co.uk

Specifications are correct at time of publication and subject to change without notice. Product images are for illustration purposes and may vary slightly from the machine supplied. © Shrink Wrapping Supplies Ltd.

CHAMBER LENGTH OPTIONS

Choose Your Chamber Length

This tunnel is available with three chamber lengths, all sharing the same 800 × 600mm chamber width & height and 0–20m/min conveyor speed — pick the length that suits your pack size and line speed.

MODEL	CHAMBER LENGTH	OVERALL MACHINE LENGTH	POWER
SM-8060S	1500mm	2500mm	32kW
SM-8060	1800mm	2800mm	38kW
SM-8060L	2500mm	3500mm	48kW

WARRANTY & SUPPORT

Support You Can Rely On

Warranty & Installation

- 12-month parts-only warranty as standard
- Installation, commissioning and operator training available on all stock machines
- Service contracts available for ongoing maintenance and support

OPTIONAL EXTRAS & CONSUMABLES

Shrink Film	Polyolefin & PVC rolls, all widths
Spare Parts	Sealing blades, heater elements & more
Consumables	Everything to keep your machine running

All available now in our online shop — shrinkwrappingsupplies.co.uk/shop

SWS
Shrink Wrapping Supplies Ltd
4A Arrow Trading Estate, Corporation Road,
Audenshaw, Manchester, M34 5LR

0161 366 5552
sales@shrinkwrappingsupplies.co.uk

Specifications are correct at time of publication and subject to change without notice. Product images are for illustration purposes and may vary slightly from the machine supplied. © Shrink Wrapping Supplies Ltd. • Page 2 of 2